


HABAŞ SINAİ VE TIBBİ GAZLAR İSTİHSAL ENDÜSTRİSİ A.Ş.



Technical Datasheet

ENGINE	
Make / model	PACCAR MX-11 EURO 6E
Type	Turbocharged, Intercooler, Diesel
Total displacement	10,8 lt.
Max. power	220 kW @ 1675 rpm
Max. torque	1350 Nm @ 900-1400 rpm
TRANSMISSION	1330 Will @ 300 1400 lpill
Make / model	ZF Ecolife, Automatic
Number of gears	6 forward, 1 reverse
AXLES	o forward, Treverse
Front axle type, capacity	ZF RL 82EC, 8.200 kg.
Rear axle type, capacity	ZF AV133/87, 13.000 kg.
Axle Ratio	6.20
SUSPENSION	6.20
	Air anxings(2) shook absorbars (2)
Front axle Rear axle	Air springs(4) shock absorbers (2)
near axie	Air springs(4), shock absorbers (4)
CTEFRING	Kneeling
STEERING	11544 / 2000
Make/ model	HEMA / 8098
Type	Servocom, hydraulic
BRAKES	T = 1 + 16 + 10 + 10 + 10 + 11
Type of Brake System	Disc brakes (front&rear) EBS,ESC, ASR, spring parking brake-rear axle
Retarder type	Intarder
TYRES	
Size	275/70 R 22,5
Quantity	6+1
Rims	8.25x22.5" /10
FUEL TANK	,
Capacity	250 lt.
Material	Aluminium / Steel
ELECTRIC SYSTEM	
Battery	2x12V 240 Ah
Alternator	24V, 2x120A
CAPACITY	,
Passenger	106(26+80), 100(26+1+73), 93(26+2+65)
Max. permissible weight	18.000 kg.
BODY	20.000 Ng.
Туре	Stainless steel, monocoque
DIMENSIONS	Staniess steet, monocoduc
A: Wheelbase	5900 mm
B: Front overhang	2778 mm
C: Rear overhang	3197 mm
D: Overall length	11875 mm
E: Overall width	2520 mm
F/G: Overall height (with A/C, w/o A/C)	3161 - 3087 mm
H: Front track	2147 mm
I: Rear track	1812 mm
Approach angle / clearance	7/7



Spare tyre